

(Currently Amended) 1. An electromechanical micromirror device, comprising:

5 a device single substrate with a 1st surface and a 2nd surface;

 a control circuitry disposed on said 1st surface of said single substrate; and

10 a micromirror section disposed on said 2nd surface of said single substrate;

 wherein said micromirror section comprises:
 a micromirror; and

15 at least ~~4~~ one support structure for supporting said micromirror.

(Currently Amended) 2. The device of claim 1, wherein:

20 said control circuitry ~~is comprising~~ a circuit selected from the group consisting of: CMOS circuits, NMOS circuits, PMOS circuits, bipolar circuits, BiCMOS circuits, DMOS circuits, HEMT circuits, amorphous silicon thin film transistor circuits, polysilicon thin film transistor circuits, SiGe transistor circuits, SiC transistor circuits, GaN transistor circuits, GaAs transistor circuits, InP transistor

25 circuits, CdSe transistor circuits, organic transistor circuits, and conjugated polymer transistor circuits.

(Currently Amended) 3. The device of claim 1, wherein:

30 said device single substrate ~~is comprising~~ a substrate selected from the group consisting of a silicon-on-insulator (SOI) substrate, a silicon substrate, a polycrystalline silicon substrate, a glass substrate, a plastic substrate, a ceramic substrate, a germanium substrate, a SiGe substrate, a SiC substrate, a sapphire substrate, a quartz substrate, a GaAs substrate, and an InP substrate.

35

January 26, 2005

(Currently Amended) 4. The device of claim 1, wherein:

said micromirror section additionally comprises at least ~~±~~ one
addressing electrode for actuating said micromirror.

5

(Currently Amended) 5. The device of claim 4, additionally comprising:

at least ~~±~~ one electrically conductive routing line integral with said
~~device~~ single substrate that connects said control circuitry to said at
least ~~±~~ one addressing electrode.

10

(Currently Amended) 6. The device of claim 5, wherein:

said at least ~~±~~ one electrically conductive routing line comprises a
via through said single substrate and a metallization in said via.

15

(Currently Amended) 7. The device of claim 1, wherein:

said ~~device~~ single substrate additionally comprises an insulating
layer between said ~~1st~~ first surface and said ~~2nd~~ second surface.

20

(Currently Amended) 8. The device of claim 1, wherein:

said micromirror ~~is~~ further comprising a metallic mirror.

25

(Currently Amended) 9. The device of claim 1, wherein:

said micromirror ~~is~~ further comprising a multilayer dielectric
mirror.

30

(Currently Amended) 10. The device of claim 1, wherein:

5 ~~the said micromirror further comprising a substantially planar~~
reflective side of ~~said micromirror is substantially planar with~~
neither recesses nor protrusions.

(Currently Amended) 11. The device of claim 1, wherein:

10 ~~the said micromirror further comprising a reflective surface of said~~
~~micromirror has having~~ no edges ~~that are~~ perpendicular to ~~the a~~
projection direction of ~~the an~~ incident light propagation vector onto
~~the plane of said device single~~ substrate.

(Currently Amended) 12. The device of claim 11, wherein:

15 said reflective surface of said micromirror ~~is in the shape of~~ further
comprising a polygon-shaped reflective surface.

(Currently Amended) 13. The device of claim 12, wherein:

20 said polygon-shaped reflective surface is selected from the group
consisting of a rectangle-shaped reflective surface and a hexagon-
shaped reflective surface.

25

January 26, 2005

(Currently Amended) 14. The device of claim 1, wherein:

5 said micromirror section additionally comprises a torsion hinge
 ~~that is disposed to support~~ underneath and supporting said
 micromirror support structure; and

~~a pair of support structures for~~ said torsion hinge that further
 comprising a pair of supporting structures for supporting ~~supports~~
10 said torsion hinge on said substrate.

(Currently Amended) 15. The device of claim 1, wherein:

15 said micromirror section additionally comprises at least ~~1~~ one
 stopping member ~~that limits the~~ for limiting a rotation of said
 micromirror.

(Currently Amended) 16. The device of claim 15, wherein:

20 said at least ~~1~~ one stopping member comprises a 1st stopping
 member ~~that limits the~~ for limiting the rotation of said micromirror
 in a 1st direction; and

25 a 2nd stopping member ~~that limits the~~ for limiting the rotation of
 said micromirror in a direction opposite to said 1st direction.

(Currently Amended) 17. An array of electromechanical micromirror devices comprising:

5 ~~a plurality of electromechanical micromirror devices disposed in a 1-dimensional or 2-dimensional array, comprising a device~~ single substrate with a 1st surface and a 2nd surface;

10 a control circuitry disposed on said 1st surface of said substrate; and

 an array of micromirror sections disposed on said 2nd surface of said single substrate wherein each said micromirror section comprises a micromirror; and

15 ~~at least 1~~ a support structure for supporting said micromirror.

(Currently Amended) 18. The array of claim 17, wherein:

20 said control circuitry ~~is comprising a circuit~~ selected from the group consisting of: CMOS circuits, NMOS circuits, PMOS circuits, bipolar circuits, BiCMOS circuits, DMOS circuits, HEMT circuits, amorphous silicon thin film transistor circuits, polysilicon thin film transistor circuits, SiGe transistor circuits, SiC transistor circuits, GaN transistor circuits, GaAs transistor circuits, InP transistor

25 circuits, CdSe transistor circuits, organic transistor circuits, and conjugated polymer transistor circuits.

(Currently Amended) 19. The array of claim 17, wherein:

5 said ~~device~~ single substrate ~~is comprising a substrate~~ selected from the group consisting of a silicon-on-insulator (SOI) substrate, a silicon substrate, a polycrystalline silicon substrate, a glass substrate, a plastic substrate, a ceramic substrate, a germanium substrate, a SiGe substrate, a SiC substrate, a sapphire substrate, a quartz substrate, a GaAs substrate, and an InP substrate.

10 (Currently Amended) 20. The array of claim 17, wherein:

 said micromirror section additionally comprises at least ~~1~~ one addressing electrode for actuating said micromirror.

15 (Currently Amended) 21. The array of claim 20, additionally comprising:

 at least ~~1~~ one electrically conductive routing line integral with said ~~device~~ single substrate that connects said control circuitry to said at least ~~1~~ one addressing electrode of at least ~~1~~ one of said
20 micromirror sections.

(Currently Amended) 22. The array of claim 21, wherein:

25 said at least ~~1~~ one electrically conductive routing line comprises a via through said single substrate and a metallization in said via.

(Currently Amended) 23. The array of claim 17, wherein:

30 said ~~device~~ single substrate additionally comprises an insulating layer between said ~~1st~~ first surface and said ~~2nd~~ second surface.

January 26, 2005

(Currently Amended) 24. The array of claim 17, wherein:

said micromirror is further comprising a metallic mirror.

5 (Currently Amended) 25. The array of claim 17, wherein:

said micromirror is further comprising a multilayer dielectric mirror.

10 (Currently Amended) 26. The array of claim 17, wherein:

~~the said micromirror further comprising a substantially planar reflective side of said micromirror is substantially planar with~~
neither recesses nor protrusions.

15 (Currently Amended) 27. The array of claim 17, wherein:

20 ~~the said micromirror further comprising a reflective surface of said micromirror has having no edges that are perpendicular to the a projection direction of the an incident light propagation vector onto the plane of said device single~~ substrate.

(Currently Amended) 28. The array of claim 27, wherein:

25 said reflective surface of said micromirror ~~is in the shape of~~ further comprising a polygon-shaped reflective surface.

(Currently Amended) 29. The array of claim 28, wherein:

30 said polygon-shaped reflective surface is selected from the group consisting of a rectangle-shaped reflective surface and a hexagon-shaped reflective surface.

January 26, 2005

(Currently Amended) 30. The array of claim 17, wherein:

5 said micromirror section additionally comprises a torsion hinge
 ~~that is disposed to support underneath and supporting~~ said
 micromirror support structure; and

~~a pair of support structures for said torsion hinge that further~~
 ~~comprising a pair of supporting structures for supporting supports~~
10 said torsion hinge on said substrate.

(Currently Amended) 31. The array of claim 17, wherein:

15 said micromirror section additionally comprises at least ~~1~~ one
 stopping member ~~that limits the~~ for limiting a rotation of said
 micromirror.

(Currently Amended) 32. The array of claim 17, wherein:

20 said at least ~~1~~ one stopping member comprises a 1st stopping
 member ~~that limits the~~ for limiting the rotation of said micromirror
 in a 1st direction; and

25 a 2nd stopping member ~~that limits the~~ for limiting the rotation of
 said micromirror in a direction opposite to said 1st direction.

(Currently Amended) 33. A spatial light modulator (SLM) comprising an array of electromechanical micromirror devices wherein said micro-mirror devices further comprising:

5 a single substrate with a 1st surface and a 2nd surface;

a control circuitry disposed on said 1st surface of said single substrate; and

10 an array of micromirror sections disposed on said 2nd surface of said single substrate wherein each said micromirror section comprises a micromirror; and

a support structure for supporting said micromirror.

15 ~~an array according to claim 17.~~

(Currently Amended) 34. A method of fabricating an array of electromechanical ~~micromirror devices~~, micromirrors comprising the steps of:

5 providing a ~~device~~ single substrate with a 1st surface and a 2nd surface;

 forming control circuitry on said 1st surface of said single substrate; and

10 ~~forming a plurality of micromirror sections on said 2nd surface of said single substrate, comprising the steps of:~~

 forming a plurality of support structures on said second surface of said single substrate and forming a plurality of micromirrors on top of and supported by said support structures. ~~for supporting micromirrors on said 2nd surface of said substrate ; and~~

~~forming a plurality of micromirrors such that each said micromirror is supported by at least 1 said support structure.~~

20 (Currently Amended) 35. The method of claim 34, wherein:

 said step of forming said control circuitry comprises a step of fabricating said control circuits selected from the group consisting of: CMOS circuits, NMOS circuits, PMOS circuits, bipolar transistor circuits, BiCMOS circuits, DMOS circuits, HEMT circuits, amorphous silicon thin film transistor circuits, polysilicon thin film transistor circuits, SiGe transistor circuits, SiC transistor circuits, GaN transistor circuits, GaAs transistor circuits, InP transistor circuits, CdSe transistor circuits, organic transistor circuits, and conjugated polymer transistor circuits.

January 26, 2005

(Currently Amended) 36. The method of claim 34, wherein:

5 said step of providing said single substrate further comprising a
 step of providing said single device substrate is selected from the a
 group consisting of a silicon-on-insulator (SOI) substrate, a silicon
 substrate, a polycrystalline silicon substrate, a glass substrate, a
 plastic substrate, a ceramic substrate, a germanium substrate, a
 SiGe substrate, a SiC substrate, a sapphire substrate, a quartz
10 substrate, a GaAs substrate, and an InP substrate.

(Currently Amended) 37. The method of claim 34, wherein:

15 said step of forming said ~~micromirror sections~~ micromirrors
 additionally comprises a step of forming a plurality of addressing
 electrodes for actuating said ~~plurality of~~ micromirrors.

(Currently Amended) 38. The method of claim 37, additionally comprising
a step of:

20 forming a plurality of electrically conductive routing lines ~~integral~~
 integrated with said ~~device single~~ substrate ~~that connects for~~
 connecting said control circuitry to said plurality of addressing
 electrodes.

25 (Currently Amended) 39. The method of claim 38, wherein said step of:

 forming said plurality of electrically conductive routing lines
 comprises the steps of:

30 forming at least \pm one via through said substrate; and

 forming a metallization in said at least \pm one via.

January 26, 2005

(Currently Amended) 40. The method of claim 34, wherein:

5 said step of providing said single substrate further comprising a
 step of providing a single device substrate additionally comprises
 an insulating layer between said 1st surface and said 2nd surface.

(Currently Amended) 41. The method of claim 34, wherein:

10 said step of forming a plurality of micromirrors comprises a step of
 forming a reflective metallic coating on said micromirrors.

(Currently Amended) 42. The method of claim 34, wherein:

15 said step of forming a plurality of micromirrors comprises a step of
 forming a reflective multilayer dielectric coating on said
 micromirrors.

January 26, 2005

(Currently Amended) 43. The method of claim 34, wherein said step of forming said ~~micromirror sections~~ micromirrors comprises the steps of:

5 forming said plurality of micromirror support structures ~~such that it is~~ embedded in a sacrificial layer of ~~sacrificial material~~;

 planarizing ~~a top surface of said layer such that said~~ sacrificial layer and ~~the top of said micromirror support structures are substantially~~ planar;

10 depositing a micromirror material on said ~~planar top surface~~;

 patterning said micromirror material to form a plurality of micromirrors; and

15 removing said sacrificial layer by an etching process.

(Currently Amended) 44. The method of claim 43, wherein:

20 said step of forming said microstructures in said sacrificial layer further comprising a step of forming said microstructures in a layer composed of a material is selected from the group consisting of a photoresist polymer, a silicon oxide, a silicon nitride, a silicon oxynitride, and an amorphous silicon.

25

(Currently Amended) 45. The method of claim 43, wherein:

said step of planarizing said top surface further comprising a step of applying comprises a chemical mechanical polishing (CMP) process.

30

(Currently Amended) 46. The method of claim 34, wherein said step of forming a plurality of micromirrors comprises a step of:

5 patterning said micromirrors to have no edges ~~that are~~
perpendicular to ~~the~~ a projection direction of ~~the~~ an incident light
propagation vector onto ~~the~~ a plane of said ~~device~~ single substrate.

(Currently Amended) 47. The method of claim 46, wherein:

10 said step of forming said micromirrors further comprising a step of
patterning at least one of each said micromirror is patterned to be
in the shape of as a polygon-shaped micromirror.

(Currently Amended) 48. The method of claim 47, wherein:

15 said step of forming said polygon-shaped micromirror is a step of
forming said micromirror either as a rectangle-shaped micromirror
or a hexagon-shaped micromirror selected from the group
20 ~~consisting of a rectangle and a hexagon.~~

(Currently Amended) 49. The method of claim 34, additionally comprising a step of:

25 forming a torsion hinge for supporting each said ~~mirror~~ support
~~structure; structures by~~ forming a hinge support followed by
forming a torsion hinge on top of and supported by said hinge
support. ~~said step comprising:~~

30 ~~forming a plurality of supports for supporting torsion hinges; and,~~
~~forming a plurality of torsion hinges.~~

(Currently Amended) 50. The method of claim 34, additionally comprising the step of:

5 forming at least ~~1~~one stopping member ~~that limits~~ for limiting a
 the rotation of ~~each~~ said micromirror.

(Currently Amended) 51. The method of claim 50, wherein said step of forming at least ~~1~~one stopping member comprises:

10 forming a 1st stopping member for limiting a the rotation of said
 micromirror in a 1st direction; and

 forming a 2nd stopping member for limiting a the rotation of said
15 micromirror in a direction opposite to said 1st direction.

(Currently Amended) 52. A method of fabricating an array of electromechanical micromirrors ~~micromirror devices~~, comprising the steps of:

20 providing a single silicon-on-insulator substrate with an epitaxial
 top silicon layer above an insulator layer, ~~and~~ supported by a
 bottom silicon layer;

 forming control circuitry on said epitaxial top silicon layer;

25 removing said bottom silicon layer, thereby exposing the insulator
 layer;

~~forming a plurality of micromirror sections on said exposed~~
 ~~insulator layer, comprising the steps of:~~

30 forming a plurality of support structures followed by ~~for~~
 ~~supporting micromirrors; and~~ forming a plurality of micromirrors
 ~~such that each said micromirror is~~ on top of and supported by at
 ~~least 1~~ said support structures ~~structure~~.

January 26, 2005

(Currently Amended) 53. The method of claim 52, wherein:

5 said step of forming said control circuitry comprises a step of
 fabricating said control circuits selected from ~~the~~ a group consisting
 of: CMOS circuits, NMOS circuits, PMOS circuits, bipolar transistor
 circuits, BiCMOS circuits, and DMOS circuits.

(Currently Amended) 54. The method of claim 52, wherein:

10 said step of removing said bottom silicon layer comprises a step of
 applying a backgrinding step to remove said bottom silicon layer.

(Currently Amended) 55. The method of claim 52, wherein:

15 said step of removing said bottom silicon layer comprises a step of
 applying a chemical mechanical polishing (CMP) step to remove
 said bottom silicon layer.

20 (Currently Amended) 56. The method of claim 52, ~~wherein said step of~~
 ~~forming said micromirror section~~ additionally comprises a step of:

 forming a plurality of addressing electrodes for actuating said
 plurality of micromirrors.

25 (Currently Amended) 57. The method of claim 56, additionally comprising
 a step of:

30 forming a plurality of electrically conductive routing lines ~~integral~~
 integrated with said device single substrate ~~that connects for~~
 connecting said control circuitry to said plurality of addressing
 electrodes.

January 26, 2005

(Currently Amended) 58. The method of claim 57, wherein said step of forming said plurality of electrically conductive routing lines comprises the steps of:

- 5 forming at least ~~1~~ one via through said substrate; and
- forming a metallization in said ~~at least 1~~ via.

10 (Currently Amended) 59. The method of claim 52, wherein said step of forming said ~~micromirror sections~~ micromirrors the steps of:

- forming said plurality of micromirror support structures ~~such that it is~~ embedded in a sacrificial layer of ~~sacrificial material~~;
- 15 planarizing a top surface of said layer ~~such that said~~ sacrificial layer and ~~the top of said micromirror support structures are substantially~~ planar;
- depositing a micromirror material on said ~~planar top surface~~;
- 20 patterning said micromirror material to form a plurality of micromirrors; and
- removing said sacrificial layer by an etching process.
- 25

(Currently Amended) 60. The method of claim 59, wherein:

- 30 said step of planarizing said top surface further comprising a step of applying ~~comprises~~ a chemical mechanical polishing (CMP) process.

January 26, 2005